

16.31 Homework 3

Prof. S. R. Hall

Issued: October 2, 2006

Due: October 11, 2006

Note: Although due October 11, please try to complete by October 6, as there will be another problem set issued then.

1. Given the plant $G(s) = 1/s^2$, design a lead compensator so that the dominant poles are located at $-2 \pm 2j$.
2. Determine the required compensation for the system

$$G(s) = \frac{K}{(s+8)(s+14)(s+20)}$$

to meet the following specifications:

- (a) Overshoot $\leq 5\%$
- (b) 10-90% rise time $t_r \leq 150$ msec

Simulate the response of this closed-loop system to a step response. Comment on the steady-state error. You should find that it is quite large.

Determine what modifications you would need to make to this controller so that the system also has

- (c) $K_p > 6$

thereby reducing the steady state error. Simulate the response of this new closed-loop system and confirm that all the specifications are met.

3. Develop a state space model for the transfer function (not in modal / diagonal form).

$$G_1(s) = \frac{(s+1)(s+2)}{(s+3)(s+4)}$$

Discuss what state vector you chose and why. Develop a “modal” state space model for this transfer function as well. Confirm that both models yield the same transfer function when you compute

$$\hat{G}(s) = C(sI - A)^{-1}B + D$$

4. A set of state-space equations is given by:

$$\begin{aligned}\dot{x}_1 &= x_1(u - \beta x_2) \\ \dot{x}_2 &= x_2(-\alpha + \beta x_1)\end{aligned}$$

where u is the input and α and β are positive constants.

- (a) Is this system linear or nonlinear, time-varying or time-invariant?
- (b) Determine the equilibrium points for this system (constant operating points), assuming a constant input $u = 1$.
- (c) Near the positive equilibrium point from (b), find a linearized state-space model of the system.