

Real Time Wireless ECG Monitoring System

Guilherme K. Kolotelo

Rogers G. Reichert

Features

- Remote monitoring of patient's heartbeat
- Low heart rate warnings
- Increased mobility by eliminating wired connections


Modular Design

- 7 Modules
 - Modulator, demodulator
 - Heartbeat detector
 - Low heart rate detector
 - Emergency signal
 - Sound amplifier
 - ECG capture board


Modulator and Demodulator

- AM transmission
 - Long distance communication
 - Less power consumption
 - Cheaper
- Carrier frequency: 455 kHz
 - Synthesization of carrier wave by separate circuitry


Carrier Wave Synthesization




Wien-Bridge Oscillator



Colpitts Oscillator




Phase-Shift Oscillator



Bubba Oscillator

Wien-Bridge Oscillator


- Few components
- Good frequency stability
- Designed values translate well into reality
- No inductors



Wien-Bridge
Oscillator



Heartbeat detector

- R peak detection
- Translates heartbeats into pulses
- Outputs signal to modulator



Low heart rate detection

- Warns user of low heart rate (adjustable)
- Outputs continuous warning tone to audio amplifier




Sound Amplifier


- Amplifies heartbeat sound and emergency signal to speaker
- Class B amplifier

ECG capture

- Developed on Lab 5



Block diagram



Schedule

- 1st week: designing of modules and circuitry
- 2nd week: building of modules and preliminary tests
- 3rd week: testing and fixing problems
- 4th week: writing of report