

Hippocampal Network Analysis Using a Multi-electrode Array (MEA)

Jonathan Karr



April 1, 2004

Outline


- Goal: To create a neuron level map of the dissociated hippocampal network
- Take correlations between stimulated neurons and all other neurons; Use result to assign unidirectional connection strength
- Will use spike sorting to connect electrode level to neuron level
- First lets see if this correlation makes sense by applying it to an artificial network
- Possible applications
 - Integrating man and machine
 - Understanding and repairing diseases/damages

Toy Network – Step I



- 9 Neurons with first order connections, the magnitude of these connections is specified
 - Any pair of neurons can be connected
- Model includes parameters for
 - Synaptic delay
 - Refractory Period Length
- Benefit of model is infinite signal to noise ratio
- Program generates nine “data” sets, each one corresponding to the “stimulation” of one of the neurons





Toy Network – Step II



Toy Network – Step III




Toy Network




Hippocampal Network – Step II


Comparison of Filtered Signal and Extracted Spikes for Electrode 2 from Stimulation of Electrode 2




Hippocampal Network – Step III



Nodal Connections with Threshold=0






Nodal Connections with Threshold=250




Spike Sorting

- Goal is to connect level of electrodes to the level of individual neurons
- Idea is to attribute spikes to individual neurons by performing convolutions and then look at the correlations between the spike trains of neurons
- Method requires the assumption no two neurons at one electrode spike with the same shape
- This requires a low neuron density as well as ten different spike shapes randomly distributed among in the culture.






Filtered Signal of Electrode 1, Threshold Factor=7.500000e-01



Filtered Signal of Electrode 1, Threshold Factor=1.250000e+00



Works Cited

- Panasonic. (2003). *MED64 Systems - Multichannel Multielectrode Array Systems for In-vitro Electro-physiology*. Retrieved March 27, 2004, from <http://www.med64.com/>.
- Eversmann B., Jenker M., Hoffman F., et al (2003). A 128x128 CMOS biosensory array for extracellular recording of neural activity. *IEEE Journal of Solid State Circuits*. 38 (12): 2306-2317.
- McAllen R.M. and Trevaks D. (2003). Are pre-ganglionic neurones recruited in a set order? *Acta Physiologica Scandinavica*. 177(3): 219-225.
- Kerman I.A., Yates B.J., and McAllen R.M. (2000). Anatomic patterning in the expression of vestibulosympathetic reflexes. *American Journal of Physiology. Regulatory, Integrative, and Comparative Physiology*. 279 (1):R109-R117.
- Cambridge Electronic Design. (2003). *Spike2, Version 5*. Retrieved March 27, 2004, from <http://www.ced.co.uk/pru.shtml>.
- Lewicki M.S. (1998). A review of methods for spike sorting: the detection and classification of neural action potentials. *Computational Neural Systems*. 9: R53-R78.
- Bierer S.M. and Anderson D.J. (1999). Multi-channel spike detection and sorting using an array processing technique. *Neurocomputing*. 26-27:945-956.
- Fee M.S., Mitra P.P., and Kleinfeld D. (1996). Automatic sorting of multiple neuronal signals in the presence of anisotropic and non-Gaussian variability. *Journal of Neuroscience Methods*. 69:175-188.
- Heitler W.J. (2004). *Dataview*. Retrieved March 27, 2004 from <http://www.st-andrews.ac.uk/~wjh/dataview.index.html>.