06E COMPRESSOR MODEL SIGNIFICANCE CHART
06ET W/SUCTION CUTOFF UNLOADING

	PRODUCT SERIES			SUCTION CUT OFF UNLOADING	MOTOR DUTY	COMP CFM & HP		ELECTRICAL CHARACTERISTICS	DESIGN CHANGES	PACKAGING
MODEL	0	6	E	2	2	5	0	4	0	0
DIGIT	1	2	3	4	5	6	7	8	9	10

1st, 2nd & 3rd DIGIT

06E COMPRESSOR

10th DIGIT PACKAGING

5th DIGIT MOTOR DUTY

0	LOW TEMP. REF.
1	LOW & MED. TEMP. REFRIG/AC/WATER COOLED
2	A/C DUTY AIR COOLED
8	SPEC. ORDER

8th DIGIT ELECT.

1	575-3-60
2	200-1-60
3	208/230/460-3-60
4	200-3-60
5	230-3-60
6	400 - 3 - 50 460 60
7	230-1-50
8	230-3-50
9	220/380-3-60
0	208/230-3-60

9th DIGIT PRODUCT DESIGN

0	OEM MODEL
1	ELECTRICAL REDESIGN
2	—
3	LONG STROKE CRANKCASE
4	ROBERTSHAW MOTOR PROTECTION
5	—
6	NO MOTOR PROTECTION
7	REFRIG. DUTY ROBERTSHAW PROTECTION
8	—
9	—

4th DIGIT – UNLOADING/APPLICATION

	NUMERAL	DESCRIPTION	
AIR CONDITIONING DUTY SUCTION CUT OFF UNLOADING	2	ONE ELECTRIC INLOADER	
	3	TWO ELECTRIC UNLOADERS	
	4	ONE PRESSURE UNLOADER	
	5	TWO PRESSURE UNLOADERS	
	6	ONE ELECTRIC UNLOADER	REVERSED CYLINDER HEAD (6 CYL.)
	7	TWO ELECTRIC UNLOADERS	
	8	ONE PRESSURE UNLOADER	
	9	TWO PRESSURE UNLOADERS	
SERVICE REPLACEMENT FOR ABOVE	T	ONE BANK WITH SUCTION CUT OFF UNLOADING CAPABILITY. BLAK OFF PLATE AND SLEEVE IN HEAD – SHIPPED FULLY LOADED.	

6th & 7th DIGIT COMP. Cu. Ft/Min.

# CYL	STD. STROKE	LONG STROKE	LONG STROKE HIGH CLEAR	SHORT STROKE
4	50	66	60 (Obsolete)	–
6	75	99	–	65

9th DIGIT SERVICE

1	THERMOTECTOR PROTECTION
2	SEE # 6
3	—
4	ROBERTSHAW SENSORS & TAPPED CYL HEADS
5	ROBERTSHAW SENSORS & TAPPED CYL. HEADS. OLD STYLE CRANKCASE
6	NEW STYLE CRANKCASE ROBERTSHAW SENSORS & TAPPED CYL HEADS
7	REFRIG. SERVICE COMP. ROBERTSHAW SENSORS