

MASSACHUSETTS INSTITUTE OF TECHNOLOGY  
Department of Mechanical Engineering

2.615 INTERNAL COMBUSTION ENGINES

Homework Set #5

Due: 3/20/2014

Problems:

- 1) Problem 6.1 of text book. Think about under the same engine speed and BMEP, why would the inlet manifold pressure and thus the Pumping MEP be different for the two fuels.
- 2) This problem is an exercise to get an idea of the flame propagation environment under typical engine condition. In the problem set directory, the simulation results for operating an engine under vehicle cruise condition (see engine specification below) are tabulated in the ascii file si\_sim.oum. The columns are explained in the matlab m-file si\_sim.m and also documented below. (If you are using matlab, executing the m-file si\_sim.m will automatically load the data file into the various variables; if you want to use Excel, you can import the file into a spread sheet.)

Engine specification:            1500 rpm; intake pressure=38 kpa;  $\lambda = 1$ ; ignition at 30° BTC  
Bore = 86 mm; stroke = 86 mm; con-rod to bore ratio = 1.58  
Clearance vol.=58.77 cc.

Plot the following quantities as a function of the mass burned fraction. Use Eq. 9.36 for the laminar flame speed calculation. The residual gas mole fraction is 20%. After the plots (by the computer), take a look at the values to appreciate the magnitude of the various quantities. (Good engineers/scientists should always know the numbers for the phenomena they are working on.)

- (i) The unburned and burned gas temperatures
  - (ii) The pressure
  - (iii) The laminar flame speed
  - (iv) The laminar flame expansion velocity
  - (v) The mass fraction burn rate  $d(x_b)/d\theta$
  - (vi) The volume of burned gas as a fraction of the charge volume
  - (vii) Assuming that the engine has a flat head and a flat piston, and assuming that the burned gas occupies a cylindrical volume of radius R and a height equals to the combustion chamber height, plot the ratio of  $2R/B$  where B is the bore. (In reality, the 'flame ball' is more likely to be roughly hemispherical at first until it touches the piston; then it will transition into a cylindrical geometry.)
- 3) Problem 9.4 of text book. The problem illustrates the effects of spark plug location and combustion chamber shape on burn rate.

---

For Problem 2, the columns of data in the file si\_sim are:

```
theta=si_sim(:,1);            %crankangle  
p     =si_sim(:,2);            %pressure (bar)  
tu    =si_sim(:,3);            %unburned gas temp (k)  
tb    =si_sim(:,4);            %burned gas temp (k)  
m_int=si_sim(:,5);            %cumulative mass inducted (g)  
m_exh=si_sim(:,6);            %cumulative mass exhausted (g)  
viv   =si_sim(:,7);            %velocity at intake valve (m/s)  
vexh  =si_sim(:,8);            %velocity at exhaust valve (m/s)  
xb    =si_sim(:,9);            %mass fraction burned  
x_net=si_sim(:,10);            %net ht rel / (LHV*fuelmass)  
qdot_h=si_sim(:,11);          %heat transfer (J/deg)  
w_pist=si_sim(:,12);          %work transfer to piston (Kj)
```