

6.1800 Spring 2025

Lecture #4: Bounded Buffers + Locks

getting many programs to communicate at once

6.1800 in the news



Emergency Management
Massachusetts Institute of Technology



No Active Message

There is currently no major emergency or disruption.

For a campus map, visit <https://whereis.mit.edu>.

[Quick Emergency Response Actions.](#)

6.1800 in the news

why does emergency.mit.net exist
when we have emergency.mit.edu?



Emergency Management
Massachusetts Institute of Technology



No Active Message

There is currently no major emergency or disruption.

For a campus map, visit <https://whereis.mit.edu>.

[Quick Emergency Response Actions.](#)

6.1800 in the news

why does `emergency.mit.net` exist
when we have `emergency.mit.edu`?

“MIT owns the domain `mit.net` and is running the emergency notification service on <http://emergency.mit.net/>. It is replicated and will normally go to the same place as <http://emergency.mit.edu/>. Having it routed through a `.net` domain gives MIT additional recovery options in case something happens to the campus network or the registrar for `.edu` domains.”



Emergency Management
Massachusetts Institute of Technology



No Active Message

There is currently no major emergency or disruption.

For a campus map, visit <https://whereis.mit.edu>.

[Quick Emergency Response Actions.](#)

operating systems enforce modularity on a single machine using **virtualization**

in order to enforce modularity + have an effective operating system, a few things need to happen

- | | | |
|---|--------|---|
| 1. programs shouldn't be able to refer to (and corrupt) each others' memory |→ | virtual memory |
| 2. programs should be able to communicate with each other |→ | assume they don't need to
(for today) |
| 3. programs should be able to share a CPU without one program halting the progress of the others |→ | assume one program per CPU
(for today) |

operating systems enforce modularity on a single machine using **virtualization**

in order to enforce modularity + have an effective operating system, a few things need to happen

- | | | |
|---|--------|--|
| 1. programs shouldn't be able to refer to (and corrupt) each others' memory |→ | virtual memory |
| 2. programs should be able to communicate with each other |→ | bounded buffers
(virtualize communication links) |
| 3. programs should be able to share a CPU without one program halting the progress of the others |→ | assume one program per CPU
(for today) |

today's goal: implement **bounded buffers** so that programs can communicate

bounded buffer: a buffer that stores (up to) **N** messages.
programs can **send** and **receive** messages via this buffer

bounded buffer: a buffer that stores (up to) **N** messages.
programs can **send** and **receive** messages via this buffer

```
// send a message by placing it in bb
send(bb, message):
  while True:
    if bb.in - bb.out < N:
      bb.buf[bb.in mod N] <- message
      bb.in <- bb.in + 1
    return
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages bb.buf can hold (assume N is large)

bounded buffer: a buffer that stores (up to) **N** messages.
programs can **send** and **receive** messages via this buffer

```
// send a message by placing it in bb
send(bb, message):
  while True:
    if bb.in - bb.out < N:
      bb.buf[bb.in mod N] <- message
      bb.in <- bb.in + 1
    return
```

```
// receive a message from bb
receive(bb):
  while True:
    if bb.out < bb.in:
      message <- bb.buf[bb.out mod N]
      bb.out <- bb.out + 1
    return message
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages bb.buf can hold (assume N is large)

bounded buffer: a buffer that stores (up to) **N** messages.
programs can **send** and **receive** messages via this buffer

```
// send a message by placing it in bb
send(bb, message):
  while True:
    if bb.in - bb.out < N:
      bb.in <- bb.in + 1
      bb.buf[bb.in mod N] <- message
    return
```

```
// receive a message from bb
receive(bb):
  while True:
    if bb.out < bb.in:
      message <- bb.buf[bb.out mod N]
      bb.out <- bb.out + 1
    return message
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages bb.buf can hold (assume N is large)

bounded buffer: a buffer that stores (up to) **N** messages.
programs can **send** and **receive** messages via this buffer

```
// send a message by placing it in bb
send(bb, message):
  while True:
    if bb.in - bb.out < N:
      bb.in <- bb.in + 1
      bb.buf[bb.in-1 mod N] <- message
    return
```

```
// receive a message from bb
receive(bb):
  while True:
    if bb.out < bb.in:
      message <- bb.buf[bb.out mod N]
      bb.out <- bb.out + 1
    return message
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages bb.buf can hold (assume N is large)

bounded buffer: a buffer that stores (up to) **N** messages.
programs can **send** and **receive** messages via this buffer

```
// send a message by placing it in bb
send(bb, message):
  while True:
    if bb.in - bb.out < N:
      bb.in <- bb.in + 1
      bb.buf[bb.in-1 mod N] <- message
    return
```

```
// receive a message from bb
receive(bb):
  while True:
    if bb.out < bb.in:
      message <- bb.buf[bb.out mod N]
      bb.out <- bb.out + 1
    return message
```

this code is **incorrect** if we
swap these two lines!

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages bb.buf can hold (assume N is large)

bounded buffer: a buffer that stores (up to) **N** messages.
programs can **send** and **receive** messages via this buffer

```
// send a message by placing it in bb
send(bb, message):
  while True:
    if bb.in - bb.out < N:
      bb.buf[bb.in mod N] <- message
      bb.in <- bb.in + 1
    return
```

```
// receive a message from bb
receive(bb):
  while True:
    if bb.out < bb.in:
      message <- bb.buf[bb.out mod N]
      bb.out <- bb.out + 1
    return message
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages bb.buf can hold (assume N is large)


what happens when multiple programs try to send?

broccoli is trying to
send message m_1



```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
6:     return
```

junebug is trying to
send message m_2



```
bb.in = 0
bb.out = 0
bb.buf = [ | | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?

broccoli is trying to
send message m_1



current line: 1

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
6:     return
```

junebug is trying to
send message m_2



current line: 1

```
bb.in = 0
bb.out = 0
bb.buf = [ | | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



current line: 1

```
// send a message by placing it in bb
-> 1: send(bb, message):
   2:   while True:
   3:     if bb.in - bb.out < N:
   4:       bb.buf[bb.in mod N] <- message
   5:       bb.in <- bb.in + 1
   6:     return
```

junebug is trying to
send message m_2



current line: 1

```
bb.in = 0
bb.out = 0
bb.buf = [ | | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



current line: 2

```
// send a message by placing it in bb
1: send(bb, message):
->2:   while True:
3:       if bb.in - bb.out < N:
4:           bb.buf[bb.in mod N] <- message
5:           bb.in <- bb.in + 1
6:       return
```

junebug is trying to
send message m_2



current line: 1

```
bb.in = 0
bb.out = 0
bb.buf = [ | | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



current line: 3

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
-> 3:     if bb.in - bb.out < N:
4:         bb.buf[bb.in mod N] <- message
5:         bb.in <- bb.in + 1
6:         return
```

junebug is trying to
send message m_2



current line: 1

```
bb.in = 0
bb.out = 0
bb.buf = [ | | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



current line: 4

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
->4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
6:       return
```

junebug is trying to
send message m_2



current line: 1

```
bb.in = 0
bb.out = 0
bb.buf = [  $m_1$  | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume N is large)

what happens when multiple programs try to send?

broccoli is trying to
send message m_1



current line: 5

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
->5:       bb.in <- bb.in + 1
6:       return
```

junebug is trying to
send message m_2



current line: 1

```
bb.in = 1
bb.out = 0
bb.buf = [ m1 | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?

broccoli is trying to
send message m_1



current line: 6

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
->6:   return
```

junebug is trying to
send message m_2



current line: 1

```
bb.in = 1
bb.out = 0
bb.buf = [  $m_1$  | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



complete

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
6:     return
```

junebug is trying to
send message m_2



current line: 1

```
bb.in = 1
bb.out = 0
bb.buf = [  $m_1$  | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume N is large)

what happens when multiple programs try to send?

broccoli is trying to
send message m_1



complete

```
// send a message by placing it in bb
-> 1: send(bb, message):
   2:   while True:
   3:     if bb.in - bb.out < N:
   4:       bb.buf[bb.in mod N] <- message
   5:       bb.in <- bb.in + 1
   6:     return
```

junebug is trying to
send message m_2



current line: 1

```
bb.in = 1
bb.out = 0
bb.buf = [ m1 | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume N is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



complete

```
// send a message by placing it in bb
1: send(bb, message):
-> 2:   while True:
3:       if bb.in - bb.out < N:
4:           bb.buf[bb.in mod N] <- message
5:           bb.in <- bb.in + 1
6:       return
```

junebug is trying to
send message m_2



current line: 2

```
bb.in = 1
bb.out = 0
bb.buf = [  $m_1$  | | | | ]
```

variables in use

bb = the bounded buffer

$message$ = the message we're trying to send/receive

$bb.in$ = total number of messages sent via this buffer

$bb.out$ = total number of messages received via this buffer

$bb.buf$ = the actual buffer for storing messages

N = total number of messages $bb.buf$ can hold (assume N is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



complete

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
-> 3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
6:       return
```

junebug is trying to
send message m_2



current line: 3

```
bb.in = 1
bb.out = 0
bb.buf = [  $m_1$  | | | | ]
```

variables in use

bb = the bounded buffer

$message$ = the message we're trying to send/receive

$bb.in$ = total number of messages sent via this buffer

$bb.out$ = total number of messages received via this buffer

$bb.buf$ = the actual buffer for storing messages

N = total number of messages $bb.buf$ can hold (assume N is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



complete

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
->4:     bb.buf[bb.in mod N] <- message
5:     bb.in <- bb.in + 1
6:   return
```

junebug is trying to
send message m_2



current line: 4

```
bb.in = 1
bb.out = 0
bb.buf = [ m1 | m2 | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



complete

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
-> 5:       bb.in <- bb.in + 1
6:       return
```

junebug is trying to
send message m_2



current line: 5

```
bb.in = 2
bb.out = 0
bb.buf = [ m1 | m2 | | | ]
```

variables in use

bb = the bounded buffer

$message$ = the message we're trying to send/receive

$bb.in$ = total number of messages sent via this buffer

$bb.out$ = total number of messages received via this buffer

$bb.buf$ = the actual buffer for storing messages

N = total number of messages $bb.buf$ can hold (assume N is large)

what happens when multiple programs try to send?

broccoli is trying to
send message m_1



complete

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
->6:   return
```

junebug is trying to
send message m_2



current line: 6

```
bb.in = 2
bb.out = 0
bb.buf = [ m1 | m2 | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



complete

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
6:     return
```

junebug is trying to
send message m_2



complete

```
bb.in = 2
bb.out = 0
bb.buf = [ m1 | m2 | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



current line: 1

```
// send a message by placing it in bb  
-> 1: send(bb, message):  
   2:   while True:  
   3:     if bb.in - bb.out < N:  
   4:       bb.buf[bb.in mod N] <- message  
   5:       bb.in <- bb.in + 1  
   6:       return
```

junebug is trying to
send message m_2



current line: 1

```
bb.in = 0  
bb.out = 0  
bb.buf = [ | | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



current line: 2

```
// send a message by placing it in bb
-> 1: send(bb, message):
   2:   while True:
   3:     if bb.in - bb.out < N:
   4:       bb.buf[bb.in mod N] <- message
   5:       bb.in <- bb.in + 1
   6:     return
```

junebug is trying to
send message m_2



current line: 1

```
bb.in = 0
bb.out = 0
bb.buf = [ | | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



current line: 2

```
// send a message by placing it in bb
1: send(bb, message):
-> 2:   while True:
3:       if bb.in - bb.out < N:
4:           bb.buf[bb.in mod N] <- message
5:           bb.in <- bb.in + 1
6:       return
```

junebug is trying to
send message m_2



current line: 2

```
bb.in = 0
bb.out = 0
bb.buf = [ | | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?

broccoli is trying to
send message m_1



current line: 3

```
// send a message by placing it in bb
1: send(bb, message):
-> 2: while True:
3:     if bb.in - bb.out < N:
4:         bb.buf[bb.in mod N] <- message
5:         bb.in <- bb.in + 1
6:     return
```

junebug is trying to
send message m_2



current line: 2

```
bb.in = 0
bb.out = 0
bb.buf = [ | | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



current line: 3

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
-> 3:     if bb.in - bb.out < N:
4:         bb.buf[bb.in mod N] <- message
5:         bb.in <- bb.in + 1
6:         return
```

junebug is trying to
send message m_2



current line: 3

```
bb.in = 0
bb.out = 0
bb.buf = [ | | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



current line: 4

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
-> 3:     if bb.in - bb.out < N:
4:         bb.buf[bb.in mod N] <- message
5:         bb.in <- bb.in + 1
6:         return
```

junebug is trying to
send message m_2



current line: 3

```
bb.in = 0
bb.out = 0
bb.buf = [ | | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



current line: 4

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
->4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
6:       return
```

junebug is trying to
send message m_2



current line: 4

```
bb.in = 0
bb.out = 0
bb.buf = [  $m_1$  | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume N is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



current line: 5

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
-> 4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
6:       return
```

junebug is trying to
send message m_2



current line: 4

```
bb.in = 0
bb.out = 0
bb.buf = [ m1 | | | | ]
```

variables in use

bb = the bounded buffer

$message$ = the message we're trying to send/receive

$bb.in$ = total number of messages sent via this buffer

$bb.out$ = total number of messages received via this buffer

$bb.buf$ = the actual buffer for storing messages

N = total number of messages $bb.buf$ can hold (assume N is large)

what happens when multiple programs try to send?

broccoli is trying to
send message m_1



current line: 5

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
-> 4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
6:       return
```

junebug is trying to
send message m_2



current line: 4

```
bb.in = 0
bb.out = 0
bb.buf = [ m2 | | | | ]
```

variables in use

bb = the bounded buffer

$message$ = the message we're trying to send/receive

$bb.in$ = total number of messages sent via this buffer

$bb.out$ = total number of messages received via this buffer

$bb.buf$ = the actual buffer for storing messages

N = total number of messages $bb.buf$ can hold (assume N is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



current line: 5

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
->5:       bb.in <- bb.in + 1
6:       return
```

junebug is trying to
send message m_2



current line: 5

```
bb.in = 1
bb.out = 0
bb.buf = [ m2 | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



current line: 6

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
->5:       bb.in <- bb.in + 1
6:       return
```

junebug is trying to
send message m_2



current line: 5

```
bb.in = 2
bb.out = 0
bb.buf = [ m2 | | | | ]
```

variables in use

bb = the bounded buffer

$message$ = the message we're trying to send/receive

$bb.in$ = total number of messages sent via this buffer

$bb.out$ = total number of messages received via this buffer

$bb.buf$ = the actual buffer for storing messages

N = total number of messages $bb.buf$ can hold (assume N is large)

what happens when multiple programs try to send?

broccoli is trying to
send message m_1



current line: 6

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
->6:   return
```

junebug is trying to
send message m_2



current line: 6

```
bb.in = 2
bb.out = 0
bb.buf = [ m2 | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

what happens when multiple programs try to send?


broccoli is trying to
send message m_1



complete

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
-> 6:   return
```

junebug is trying to
send message m_2



current line: 6

```
bb.in = 2
bb.out = 0
bb.buf = [  $m_2$  | | | | ]
```

variables in use

bb = the bounded buffer

$message$ = the message we're trying to send/receive

$bb.in$ = total number of messages sent via this buffer

$bb.out$ = total number of messages received via this buffer

$bb.buf$ = the actual buffer for storing messages

N = total number of messages $bb.buf$ can hold (assume N is large)

what happens when multiple programs try to send?

broccoli is trying to
send message m_1



complete

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       bb.buf[bb.in mod N] <- message
5:       bb.in <- bb.in + 1
6:       return
```

junebug is trying to
send message m_2



complete

```
bb.in = 2
bb.out = 0
bb.buf = [ m2 | | | | ]
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

this implementation of send and receive only works with a single sender and receiver; it can introduce **race conditions with multiple senders**

```
// send a message by placing it in bb
send(bb, message):
  while True:
    if bb.in - bb.out < N:
      bb.buf[bb.in mod N] <- message
      bb.in <- bb.in + 1
    return
```

```
// receive a message from bb
receive(bb):
  while True:
    if bb.out < bb.in:
      message <- bb.buf[bb.out mod N]
      bb.out <- bb.out + 1
    return message
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages bb.buf can hold (assume N is large)

```
// send a message by placing it in bb
send(bb, message):
  while True:
    if bb.in - bb.out < N:
      bb.buf[bb.in mod N] <- message
      bb.in <- bb.in + 1
    return
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages bb.buf can hold (assume N is large)

```
// send a message by placing it in bb
send(bb, message):
  while True:
    if bb.in - bb.out < N:
      bb.buf[bb.in mod N] <- message
      bb.in <- bb.in + 1
    return
```

our earlier problem stemmed from the fact that a program could be interrupted after adding `message` to `bb.buf`, but before incrementing `bb.in`

variables in use
`bb` = the bounded buffer
`message` = the message we're trying to send/receive
`bb.in` = total number of messages sent via this buffer
`bb.out` = total number of messages received via this buffer
`bb.buf` = the actual buffer for storing messages
`N` = total number of messages `bb.buf` can hold (assume `N` is large)

```
// send a message by placing it in bb
send(bb, message):
  while True:
    if bb.in - bb.out < N:
      bb.buf[bb.in mod N] <- message
      bb.in <- bb.in + 1
    return
```

our earlier problem stemmed from the fact that a program could be interrupted after adding `message` to `bb.buf`, but before incrementing `bb.in`

(*in fact*, a program could be interrupted *while* incrementing `bb.in`; remember that `bb.in <- bb.in + 1` is multiple lines in assembly)

variables in use
`bb` = the bounded buffer
`message` = the message we're trying to send/receive
`bb.in` = total number of messages sent via this buffer
`bb.out` = total number of messages received via this buffer
`bb.buf` = the actual buffer for storing messages
`N` = total number of messages `bb.buf` can hold (assume `N` is large)

locks allow only one CPU to be inside a piece of code at a time.
programs can **acquire** and **release** a lock

```
// send a message by placing it in bb
send(bb, message):
  while True:
    if bb.in - bb.out < N:
      bb.buf[bb.in mod N] <- message
      bb.in <- bb.in + 1
    return
```

our earlier problem stemmed from the fact
that a program could be interrupted after
adding **message** to **bb.buf**, but before
incrementing **bb.in**

(*in fact*, a program could be interrupted *while*
incrementing **bb.in**; remember that **bb.in <-**
bb.in + 1 is multiple lines in assembly)

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

locks allow only one CPU to be inside a piece of code at a time.
programs can **acquire** and **release** a lock

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       acquire(bb.lock)
5:       bb.buf[bb.in mod N] <- message
6:       bb.in <- bb.in + 1
7:       release(bb.lock)
8:   return
```

our earlier problem stemmed from the fact
that a program could be interrupted after
adding `message` to `bb.buf`, but before
incrementing `bb.in`

variables in use

`bb` = the bounded buffer

`message` = the message we're trying to send/receive

`bb.in` = total number of messages sent via this buffer

`bb.out` = total number of messages received via this buffer

`bb.buf` = the actual buffer for storing messages

`N` = total number of messages `bb.buf` can hold (assume `N` is large)

`bb.lock` = lock intended to protect the bounded buffer

locks allow only one CPU to be inside a piece of code at a time.
programs can **acquire** and **release** a lock

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       acquire(bb.lock)
5:       bb.buf[bb.in mod N] <- message
6:       bb.in <- bb.in + 1
7:       release(bb.lock)
8:   return
```

our earlier problem stemmed from the fact
that a program could be interrupted after
adding `message` to `bb.buf`, but before
incrementing `bb.in`

now, only one
program can be “in”
this section of the
code at a time

variables in use

`bb` = the bounded buffer

`message` = the message we’re trying to send/receive

`bb.in` = total number of messages sent via this buffer

`bb.out` = total number of messages received via this buffer

`bb.buf` = the actual buffer for storing messages

`N` = total number of messages `bb.buf` can hold (assume `N` is large)

`bb.lock` = lock intended to protect the bounded buffer

locks allow only one CPU to be inside a piece of code at a time.
programs can **acquire** and **release** a lock

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       acquire(bb.lock)
5:       bb.buf[bb.in mod N] <- message
6:       bb.in <- bb.in + 1
7:       release(bb.lock)
8:   return
```

our earlier problem stemmed from the fact
that a program could be interrupted after
adding **message** to **bb.buf**, but before
incrementing **bb.in**

now, only one
program can be “in”
this section of the
code at a time

question: suppose the buffer has room for
exactly one more message. program A and
program B each call send. what might
happen?

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

bb.lock = lock intended to protect the bounded buffer

locks allow only one CPU to be inside a piece of code at a time.
programs can **acquire** and **release** a lock

```
// send a message by placing it in bb
1: send(bb, message):
2:   while True:
3:     if bb.in - bb.out < N:
4:       acquire(bb.lock)
5:       bb.buf[bb.in mod N] <- message
6:       bb.in <- bb.in + 1
7:       release(bb.lock)
8:   return
```

our earlier problem stemmed from the fact
that a program could be interrupted after
adding **message** to **bb.buf**, but before
incrementing **bb.in**

now, only one
program can be “in”
this section of the
code at a time

problem: second sender could end up
writing to full buffer

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

bb.lock = lock intended to protect the bounded buffer

locks allow only one CPU to be inside a piece of code at a time.
programs can **acquire** and **release** a lock

```
// send a message by placing it in bb
send(bb, message):
    acquire(bb.lock)
    while True:
        if bb.in - bb.out < N:
            bb.buf[bb.in mod N] <- message
            bb.in <- bb.in + 1
            release(bb.lock)
    return
```

the previous problem stemmed from the fact that programs checked whether **bb.buf** had space before acquiring **bb.lock**

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

bb.lock = lock intended to protect the bounded buffer

locks allow only one CPU to be inside a piece of code at a time.
programs can **acquire** and **release** a lock

```
// send a message by placing it in bb
send(bb, message):
    acquire(bb.lock)
    while True:
        if bb.in - bb.out < N:
            bb.buf[bb.in mod N] <- message
            bb.in <- bb.in + 1
            release(bb.lock)
    return
```

```
// receive a message from bb
receive(bb):
    acquire(bb.lock)
    while True:
        if bb.out < bb.in:
            message <- bb.buf[bb.out mod N]
            bb.out <- bb.out + 1
            release(bb.lock)
    return message
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

bb.lock = lock intended to protect the bounded buffer

locks allow only one CPU to be inside a piece of code at a time.
programs can **acquire** and **release** a lock

```
// send a message by placing it in bb
send(bb, message):
    acquire(bb.lock)
    while True:
        if bb.in - bb.out < N:
            bb.buf[bb.in mod N] <- message
            bb.in <- bb.in + 1
            release(bb.lock)
    return
```

```
// receive a message from bb
receive(bb):
    acquire(bb.lock)
    while True:
        if bb.out < bb.in:
            message <- bb.buf[bb.out mod N]
            bb.out <- bb.out + 1
            release(bb.lock)
    return message
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

bb.lock = lock intended to protect the bounded buffer

question: suppose the buffer is full.
program A calls send, and program B calls
receive. what might happen?

locks allow only one CPU to be inside a piece of code at a time.
programs can **acquire** and **release** a lock

```
// send a message by placing it in bb
send(bb, message):
    acquire(bb.lock)
    while True:
        if bb.in - bb.out < N:
            bb.buf[bb.in mod N] <- message
            bb.in <- bb.in + 1
            release(bb.lock)
    return
```

```
// receive a message from bb
receive(bb):
    acquire(bb.lock)
    while True:
        if bb.out < bb.in:
            message <- bb.buf[bb.out mod N]
            bb.out <- bb.out + 1
            release(bb.lock)
    return message
```

problem: deadlock* if buffer is full

variables in use
bb = the bounded buffer
message = the message we're trying to send/receive
bb.in = total number of messages sent via this buffer
bb.out = total number of messages received via this buffer
bb.buf = the actual buffer for storing messages
N = total number of messages bb.buf can hold (assume N is large)
bb.lock = lock intended to protect the bounded buffer

locks allow only one CPU to be inside a piece of code at a time.
programs can **acquire** and **release** a lock

```
// send a message by placing it in bb
send(bb, message):
    acquire(bb.lock)
    while True:
        if bb.in - bb.out < N:
            bb.buf[bb.in mod N] <- message
            bb.in <- bb.in + 1
            release(bb.lock)
    return
```

```
// receive a message from bb
receive(bb):
    acquire(bb.lock)
    while True:
        if bb.out < bb.in:
            message <- bb.buf[bb.out mod N]
            bb.out <- bb.out + 1
            release(bb.lock)
    return message
```

problem: deadlock* if buffer is full

*in 6.1800, we'll use "deadlock" to mean "two programs are waiting on each other, and neither can make progress until the other one does"

variables in use
bb = the bounded buffer
message = the message we're trying to send/receive
bb.in = total number of messages sent via this buffer
bb.out = total number of messages received via this buffer
bb.buf = the actual buffer for storing messages
N = total number of messages bb.buf can hold (assume N is large)
bb.lock = lock intended to protect the bounded buffer

locks allow only one CPU to be inside a piece of code at a time.
programs can **acquire** and **release** a lock

```
// send a message by placing it in bb
send(bb, message):
    acquire(bb.lock)
    while bb.in - bb.out >= N:
        release(bb.lock)
        acquire(bb.lock)
    bb.buf[bb.in mod N] <- message
    bb.in <- bb.in + 1
    release(bb.lock)
    return
```

```
// receive a message from bb
receive(bb):
    acquire(bb.lock)
    while bb.out >= bb.in:
        release(bb.lock)
        acquire(bb.lock)
    message <- bb.buf[bb.out mod N]
    bb.out <- bb.out + 1
    release(bb.lock)
    return message
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

bb.lock = lock intended to protect the bounded buffer

locks allow only one CPU to be inside a piece of code at a time.
programs can **acquire** and **release** a lock

```
// send a message by placing it in bb
```

```
send(bb, message):
```

```
    acquire(bb.lock)
```

```
    while bb.in - bb.out >= N:
```

```
        release(bb.lock)
```

```
        acquire(bb.lock)
```

give up the lock to allow other
programs to access the buffer

```
    bb.buf[bb.in mod N] <- message
```

```
    bb.in <- bb.in + 1
```

```
    release(bb.lock)
```

```
    return
```

```
// receive a message from bb
```

```
receive(bb):
```

```
    acquire(bb.lock)
```

```
    while bb.out >= bb.in:
```

```
        release(bb.lock)
```

```
        acquire(bb.lock)
```

```
    message <- bb.buf[bb.out mod N]
```

```
    bb.out <- bb.out + 1
```

```
    release(bb.lock)
```

```
    return message
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages bb.buf can hold (assume N is large)

bb.lock = lock intended to protect the bounded buffer

locks allow only one CPU to be inside a piece of code at a time.
programs can **acquire** and **release** a lock

```
// send a message by placing it in bb
```

```
send(bb, message):
```

```
    acquire(bb.lock)
```

```
    while bb.in - bb.out >= N:
```

```
        release(bb.lock)
```

```
        acquire(bb.lock)
```

give up the lock to allow other
programs to access the buffer

```
    bb.buf[bb.in mod N] <- message
```

```
    bb.in <- bb.in + 1
```

```
    release(bb.lock)
```

```
    return
```

```
// receive a message from bb
```

```
receive(bb):
```

```
    acquire(bb.lock)
```

```
    while bb.out >= bb.in:
```

```
        release(bb.lock)
```

```
        acquire(bb.lock)
```

```
    message <- bb.buf[bb.out mod N]
```

```
    bb.out <- bb.out + 1
```

```
    release(bb.lock)
```

```
    return message
```

variables in use

bb = the bounded buffer

message = the message we're trying to send/receive

bb.in = total number of messages sent via this buffer

bb.out = total number of messages received via this buffer

bb.buf = the actual buffer for storing messages

N = total number of messages **bb.buf** can hold (assume **N** is large)

bb.lock = lock intended to protect the bounded buffer

if you are unsatisfied by the
performance of this code, *that's*
okay; we're going to revisit it

locks create **atomic actions**. deciding what actions should be atomic, while balancing **performance**, is a challenge

locks create **atomic actions**. deciding what actions should be atomic, while balancing **performance**, is a challenge

```
// move a file from one directory to another
move(dir1, dir2, filename):
    unlink(dir1, filename)
    link(dir2, filename)
```

locks create **atomic actions**. deciding what actions should be atomic, while balancing **performance**, is a challenge

```
// move a file from one directory to another
move(dir1, dir2, filename):
    unlink(dir1, filename)
    link(dir2, filename)
```

variables in use

dir1 = the directory to move the file from

dir2 = the directory to move the file to

filename = the absolute path of the file

locks create **atomic actions**. deciding what actions should be atomic, while balancing **performance**, is a challenge

```
// move a file from one directory to another
move(dir1, dir2, filename):
    acquire(fs_lock)
    unlink(dir1, filename)
    link(dir2, filename)
    release(fs_lock)
```

variables in use

dir1 = the directory to move the file from

dir2 = the directory to move the file to

filename = the absolute path of the file

fs_lock = a global lock held whenever a program interacts with the filesystem

locks create **atomic actions**. deciding what actions should be atomic, while balancing **performance**, is a challenge

```
// move a file from one directory to another
move(dir1, dir2, filename):
    acquire(fs_lock)
    unlink(dir1, filename)
    link(dir2, filename)
    release(fs_lock)
```

problem: poor performance

variables in use

dir1 = the directory to move the file from

dir2 = the directory to move the file to

filename = the absolute path of the file

fs_lock = a global lock held whenever a program interacts with the filesystem

locks create **atomic actions**. deciding what actions should be atomic, while balancing **performance**, is a challenge

```
// move a file from one directory to another
move(dir1, dir2, filename):
    acquire(dir1.lock)
    unlink(dir1, filename)
    release(dir1.lock)
    acquire(dir2.lock)
    link(dir2, filename)
    release(dir2.lock)
```

variables in use

dir1 = the directory to move the file from

dir2 = the directory to move the file to

filename = the absolute path of the file

dir1.lock, **dir2.lock** = directory-specific locks

locks create **atomic actions**. deciding what actions should be atomic, while balancing **performance**, is a challenge

```
// move a file from one directory to another
move(dir1, dir2, filename):
    acquire(dir1.lock)
    unlink(dir1, filename)
    release(dir1.lock)
    acquire(dir2.lock)
    link(dir2, filename)
    release(dir2.lock)
```

problem: exposes inconsistent state

variables in use

dir1 = the directory to move the file from

dir2 = the directory to move the file to

filename = the absolute path of the file

dir1.lock, **dir2.lock** = directory-specific locks

locks create **atomic actions**. deciding what actions should be atomic, while balancing **performance**, is a challenge

```
// move a file from one directory to another
move(dir1, dir2, filename):
    acquire(dir1.lock)
    acquire(dir2.lock)
    unlink(dir1, filename)
    link(dir2, filename)
    release(dir1.lock)
    release(dir2.lock)
```

variables in use

dir1 = the directory to move the file from

dir2 = the directory to move the file to

filename = the absolute path of the file

dir1.lock, **dir2.lock** = directory-specific locks

locks create **atomic actions**. deciding what actions should be atomic, while balancing **performance**, is a challenge

```
// move a file from one directory to another
move(dir1, dir2, filename):
    acquire(dir1.lock)
    acquire(dir2.lock)
    unlink(dir1, filename)
    link(dir2, filename)
    release(dir1.lock)
    release(dir2.lock)
```

problem: deadlock

variables in use

dir1 = the directory to move the file from

dir2 = the directory to move the file to

filename = the absolute path of the file

dir1.lock, **dir2.lock** = directory-specific locks

locks create **atomic actions**. deciding what actions should be atomic, while balancing **performance**, is a challenge

```
// move a file from one directory to another
move(dir1, dir2, filename):
    if dir1.inum < dir2.inum:
        acquire(dir1.lock)
        acquire(dir2.lock)
    else:
        acquire(dir2.lock)
        acquire(dir1.lock)
    unlink(dir1, filename)
    link(dir2, filename)
    release(dir1.lock)
    release(dir2.lock)
```

variables in use

dir1 = the directory to move the file from

dir2 = the directory to move the file to


filename = the absolute path of the file

dir1.lock, **dir2.lock** = directory-specific locks

dir1.inum, **dir2.inum** = i-numbers for each directory

locks create **atomic actions**. deciding what actions should be atomic, while balancing **performance**, is a challenge

```
// move a file from one directory to another
move(dir1, dir2, filename):
    if dir1.inum < dir2.inum:
        acquire(dir1.lock)
        acquire(dir2.lock)
    else:
        acquire(dir2.lock)
        acquire(dir1.lock)
    unlink(dir1, filename)
    link(dir2, filename)
    release(dir1.lock)
    release(dir2.lock)
```



could release `dir1.lock`
here instead

variables in use

`dir1` = the directory to move the file from

`dir2` = the directory to move the file to

`filename` = the absolute path of the file

`dir1.lock`, `dir2.lock` = directory-specific locks

`dir1.inum`, `dir2.inum` = i-numbers for each directory

to believe that all of this works, we should understand the implementations of **acquire** and **release**

we can treat a lock as a flag that is true (1) when the lock is held and false (0) otherwise

acquire(**lock**):

release(**lock**):

variables in use

lock = the lock being acquired/released

to believe that all of this works, we should understand the implementations of **acquire** and **release**

we can treat a lock as a flag that is true (1) when the lock is held and false (0) otherwise

```
acquire(lock):
```

```
release(lock):
```

```
    lock = 0
```

to believe that all of this works, we should understand the implementations of **acquire** and **release**

we can treat a lock as a flag that is true (1) when the lock is held and false (0) otherwise

acquire(**lock**):

release(**lock**):

lock = 0

lock is released; no
program holds it

to believe that all of this works, we should understand the implementations of **acquire** and **release**

we can treat a lock as a flag that is true (1) when the lock is held and false (0) otherwise

```
acquire(lock):  
    while lock != 0:  
        do nothing
```

```
release(lock):  
    lock = 0
```

lock is released; no
program holds it

to believe that all of this works, we should understand the implementations of **acquire** and **release**

we can treat a lock as a flag that is true (1) when the lock is held and false (0) otherwise

another program holds
lock; it can't be
acquired

```
acquire(lock):  
    while lock != 0:  
        do nothing
```

```
release(lock):  
    lock = 0
```

lock is released; no
program holds it

to believe that all of this works, we should understand the implementations of **acquire** and **release**

we can treat a lock as a flag that is true (1) when the lock is held and false (0) otherwise

another program holds
lock; it can't be
acquired

```
acquire(lock):  
    while lock != 0:  
        do nothing  
    lock = 1
```

```
release(lock):  
    lock = 0
```

lock is released; no
program holds it

to believe that all of this works, we should understand the implementations of **acquire** and **release**

we can treat a lock as a flag that is true (1) when the lock is held and false (0) otherwise

another program holds
lock; it can't be
acquired

```
acquire(lock):  
    while lock != 0:  
        do nothing  
    lock = 1
```

```
release(lock):  
    lock = 0
```

lock is released; no
program holds it

problem: race condition
(need locks to implement locks!)

to believe that all of this works, we should understand the implementations of **acquire** and **release**

we can treat a lock as a flag that is true (1) when the lock is held and false (0) otherwise

	acquire(lock):	release(lock):	
another program holds	while lock != 0:	lock = 0	lock is released; no
lock ; it can't be	<i>do nothing</i>		program holds it
acquired	lock = 1		

implementing locks requires hardware support — namely an atomic exchange operation. much like how the MMU needs the physical address of page tables, and DNS clients need to know the IP address of a root server

to believe that all of this works, we should understand the implementations of **acquire** and **release**

we can treat a lock as a flag that is true (1) when the lock is held and false (0) otherwise

```
acquire(lock):
```

```
do:
```

```
  r <- 1
```

```
  XCHG r, lock
```

```
  while r == 1
```

```
release(lock):
```

```
  lock = 0
```

XCHG atomically swaps the value of **r** and **lock**; it cannot be interrupted in the middle of this action

implementing locks requires hardware support — namely an atomic exchange operation. much like how the MMU needs the physical address of page tables, and DNS clients need to know the IP address of a root server

```
// send a message by placing it in bb
send(bb, message):
    acquire(bb.lock)
    while bb.in - bb.out >= N:
        release(bb.lock)
        acquire(bb.lock)
    bb.buf[bb.in mod N] <- message
    bb.in <- bb.in + 1
    release(bb.lock)
    return
```

```
// receive a message from bb
receive(bb):
    acquire(bb.lock)
    while bb.out >= bb.in:
        release(bb.lock)
        acquire(bb.lock)
    message <- bb.buf[bb.out mod N]
    bb.out <- bb.out + 1
    release(bb.lock)
    return message
```

lingering **performance issue**: this is a *lot* of releasing and acquiring, especially if the buffer remains full (or empty) for some time. we will address this in the next lecture

there is also something unsatisfying about locks, in that we often need a global understanding of how they're used; we'll come back to that later in 6.1800

...Since these filesystems may contain millions or hundreds of millions of files, most of which are inspected exactly once and found not to have changed, it generates a lot of "garbage" in kernel memory which must eventually be reclaimed. The kernel only actively collects this garbage, which it does by means of a pseudo-LRU queue, when it runs into a configured limit. **There is a broad-scope mutex which protects this queue, and one of the issues is that it is held too long while the garbage-collector is running, which causes any process on the system that needs to open a file -- including the NFS server process -- to block.**

- email from Garrett Wollman in CSAIL, Fall 2023

operating systems enforce modularity on a single machine

in order to enforce modularity + have an effective operating system, a few things need to happen

- | | | |
|---|--------|--|
| 1. programs shouldn't be able to refer to (and corrupt) each others' memory |→ | virtualize memory |
| 2. programs should be able to communicate with each other |→ | bounded buffers
(virtualize communication links) |
| 3. programs should be able to share a CPU without one program halting the progress of the others |→ | assume one program per CPU
(for today) |

bounded buffers allow programs to communicate, completing the second step of enforcing modularity on a single machine. dealing with **concurrency** opens up a number of new challenges

locks allow us to implement **atomic actions**. determining the correct locking discipline can be tough thanks to race conditions, deadlock, and performance issues

notice that we have **choices** about how apply locks (e.g., fine-grained, coarse-grained). those choices **impact** the performance and simplicity of our systems, which in turn impacts users, developers, and beyond

(and right now, performance and simplicity appear to be at odds)